

MO-600 & MO-735 Series

Home Sergers

JUKI

JUKI HOME SERGERS ARE EASY-TO-USE AND ARE KNOWN FOR THEIR INDUSTRIAL MACHINE TECHNOLOGY AND HIGH QUALITY STITCHING



A World Leader in Sewing Machine Technology



M0-655

2-Needle, 2/3/4/5 Thread Overlock with Automatic Rolled Hemming, Differential Feed and Chainstitch

With this 5 thread serger you can meet new sewing challenges with a wide range of overlock stitch variations. The M0-655 performs a 2-thread chainstitch making it possible to sew a secure 5-thread safety stitch as well as differential feed and automatic rolled hemming!

MO-654DE

2-Needle, 2/3/4 Thread Overlock with Automatic Rolled Hemming and Differential Feed

Expand your sewing capabilities with the M0-654DE 4-thread machine offering a variety of stitch selections as well as differential feed and automatic rolled hemming. Create the latest fashion styles and home décor items sewing light to heavy weight fabrics.





M0-644D

2-Needle, 2/3/4 Thread Overlock with Automatic Rolled Hemming and Differential Feed

Let your creativity soar with one of Juki's most popular machines. This 4-thread overlock with differential feed and automatic rolled hemming was designed with economy and performance in mind to sew all the popular overlock stitch variations.

M0-623

1-Needle, 2/3 Thread Overlock with Automatic Rolled Hemming

A beginner or advanced sewer can create simple projects or elegant fashions with the MO-623 single needle, 2/3 thread serger with automatic rolled hemming. Designed with Juki industrial technology, this economical unit gives unbelievable serger performance.





MO-735


2-Needle, 2/3/4/5 Thread Overlock with Chainstitch and Coverstitch.

With the M0-735 you can advance your serging applications to include chainstitch, 5 thread safety stitch, and 2 or 3 needle coverstitch. The M0-735 can handle all types of fabrics from ultra light weight to heavy weight. Achieve virtually every serger technique and decorative stitch you've imaged with the M0-735!

FEATURES

Adjustable Stitch Length

by simply turning the knob located inside the machine within the range of 1 to 4 mm. (MO-623/644D).





MO-623/644D MO-654DE/655/735



located on the exterior, left hand side of the machine.

For MO-654DE/655/735 models the turn dial is located on the exterior right hand side.



MO-654DE/655/735

Automatic Rolled Hemming

can now be created quickly and easily with built-in fingertip control. There is no need to change the foot or plate.



Lower Looper Threader

allows for easy threading in seconds simply slide your thread into a slot and snap the looper back in place. (MO-654DE/655 only)



Lower Knife Adjustment Knob

adjusts the lower knife quickly to change the width of fabric in the seam allowance, for perfect seams and rolled edges.



MO-654DE/655

Heavy-Duty Knife System operates with a dedicated drive to

assure consistent and easy cutting of light to heavy weight fabrics.



Upper Knife Releasing System

removes the upper knife so that threading is made safer and easier.



Multi-Purpose Foot

comes equipped with a slotted tape guide which can be used to sew woven tape, elastic, seguins and ribbon.



Color-Coded Threading Guides

throughout the machine make threading easy and efficient.



Chain Looper Threader

is out of the way when serging. To thread, simply push a button and the looper snaps down for easy threading. (MO-655 only)



OPTIONAL ATTACHMENTS

Blind Stitch Presser Foot: Part No. A9810-634-0A0A (For use with right needle only)



Universal Blind Stitch Presser Foot: Part No. A9521-634-0A0

Part No. A9521-634-0A0A (For use with left or right needle)



Elasticator Presser Foot: Part No. A9815-655-0A0A



Cording Presser Foot: Part No. A9820-655-0A0A



Beading Presser Foot: Part No. A9870-634-0A0A



Piping Presser Foot: Part No. A9865-655-0A0A



Gathering Presser Foot: Part No. A9860-655-0A0B



Curved Beading Presser Foot Part No. A9511-634-0A0A



Attachments are also available in 3, 6 and 8 piece sets

Create the latest fashions or decorative home items and crafts with the M0-600 and M0-700 Series Home Sergers.

STANDARD SPECIFICATIONS

	M0-623	M0-644D	MO-654DE	M0-655	M0-735				
Sewing Speed	Maximum 1,500 spm								
Number of Threads	2/3 Threads 2/3/4 Threads 2/3/4 Threads 2/3/4/5 Threads				Threads				
Needle	Household Machine Size 11 or 14								
Overlocking Width	Standard: 4 mm Rolled Hem: 1.0 - 1.5 mm	Left Needle: 6 mm / Right Needle: 4 mm Rolled Hem: 2 mm	Left Needle: 6 mm / Right Needle: 4 mm Rolled Hem: 2 mm	Chain Needle: 10 mm Left Needle: 6 mm / Right Needle: 4 mm Rolled Hem: 2 mm	Coverstitch: 2.5-5mm Chain Needle: 10mm Left Needle: 7mm / Right Needle: 5mm Rolled Hem: 2mm				
Stitch Length	1 - 4 mm (Standard: 2.5 mm) / Rolled Hem: 1.0 - 1.5 mm								
Differential Feed	— 0.7 - 2.0 Ratio								
Tension	Industrial Type Dial / 1 Rotation Lay-In Tension								
Built-In Rolled Hemming	2 or 3 Thread Right (Narrow) or Left (Wide) Needle / 2 or 3 Thread								
Flatlock	2 or 3 Thread Right or Left Needle / 2 or 3 Thread 2 or 3 Thread								
Universal Presser Foot	Tape, Ribbon, Narrow Elastic Application								
Presser Foot Lift	5 mm								
Dimensions	270 mm (w) x 260 mm (d) x 295 mm (h) 270 mm (w) x 340 mm (d) x 295 mm (h		270 mm (w) x 345 mm (d) x 295 mm (h)	315 mm (w) x 345 mm (d) x 295 mm (h)	305mm (w) x260mm (d) x 286mm (h)				
Weight	7.0 Kg	(15 lbs)	7.0 Kg (15 lbs)	7.2 Kg (15.5 lbs)	9 kg (19.8 lbs)				

STITCH VARIATIONS

Model		The state of the s	The state of the s	and the second s	/	A STANKED	7				1330
	2-Thread Chainstich	5-Thread Safety Stitch	4-Thread Overlock	3-Thread Flatlock	3-Thread Narrow Overlock- 4mm	Frill 3-Thread Rolled Hem w/ Diff. Feed	3-Thread Rolled Hem	3-Thread Overlock	2-Thread Rolled Hem	2-Thread Overcast	3-Needle Coverstitch
MO-623				_	_		_	_	_	_	
MO-644D			_	_	_	_	_	_	_	_	
MO-654DE			_	_	_	_	_	_	_	_	
MO-655	_	_	_	_	_	_	_	_	_	_	
M0-735	_	_	_	_	_	_	_	_	_	_	_

MACHINE COMPARISON

	M0-623	M0-644D	M0-654DE	M0-655	M0-735	
Adjustable Stitch Length	Standard					
Lower Knife Adjustment	Standard					
Heavy Duty Knife System	Standard					
Automatic Rolled Hemming	Standard					
Sewing Light	Standard					
Mulit-purpose Foot	Standard					
Sewing Width Gauge	Standard					
Color-Coded Threading Guides	Standard					
Thread Tension Dials	Standard					
2/3 Thread Converter	Opti	onal	Standard			
Adjustable Differential Feed	n/a	Stand		dard		
Lower Looper Threader	n,	/a	Standard			
Chain Looper Threader	n/a			Standard		
Auxiliary Bed	n/a			Standard		

Contact Juki America, Inc. for the dealer nearest you or visit our website at www.juki.com



8500 N.W. 17th Street
Doral, FL 33126
Tel: 305.594.0059 Fax: 305.594.0720
Home Division E-mail: home@juki.com

Subject to change without prior notice